

## **PV Disconnect 1000-40-5** Connection box with DC disconnect

#### Description

An outdoor rated, combining connection box with DC disconnect switch that allows up to 5 strings of PV modules to be connected safely to a solar pump system.

### Features

- DC rated disconnect to provide safe isolation of the system
- Combining function, allows 5 strings to be connected to the solar pump system
- Robust weather proof housing designed to make installation simple
- Lockable to secure the system during maintenance (power locked off)
- For professional installation of pumping systems
- Internal touch protection with screws
- Designed to be used with the LORENTZ PSk range of systems

#### Ordering and shipping information

- Item no: 19-000121
- Product name: PV Disconnect 1000-40-5
- Packed volume: 0.015 m<sup>3</sup> (0.54 ft<sup>3</sup>)
- Packed weight: 3.2 kg (7.1 lbs)

#### Approvals and standards

• Switch IEC 60947-3



#### Technical data / Specifications

Maximum voltage	1000 V DC	
Maximum current per string	40 A	
Maximum total current	40 A	
Number of strings.	5	
Input cables	4 - 10 mm <sup>2</sup>	AWG 12 - 8
Output cables	4 - 16 mm <sup>2</sup>	AWG 12 - 6
PG glands (input)	10 x M16	
PG glands (output)	2 x PG11	
Environmental protection	IP68	NEMA6
Housing material	Polycarbonate	

# CE

#### **BERNT LORENTZ GmbH**

Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany Tel. +49(0) 4193 8806 - 700, www.lorentz.de



V210201

whoto may differ from actual product



#### **Mounting options**

- Wall mount using 4 holes with weather protection
- Designed for optional pole mounting. Mounting points are pre-marked inside the housing.



### **Dimensions and weight**

- See diagram for mm sizes
- Max height 220 mm (8.66")
- Max width 307 mm (12.1")
- depth 140 mm (5.5")
- Weight 2.67 kg (5.9 lbs)





**BERNT LORENTZ GmbH** 

Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany Tel. +49 (0) 4193 8806 - 700, www.lorentz.de

